

Remomedi PickupPharmacy 2023 Product Line



Remomedi PickupPharmacy lockers are designed for pharmacy chains, independent pharmacies and hospitals:

- Burglar and fireproof steel structure
- Build-in encrypted wireless communication
- Temperature zones 2–8°C and 15–25°C
- Build-in multipoint temperature control and alert system
- Works together with access control in a draught lobby
- Modular, expandable

The **Climatop model** is designed to be used in locations where ambient (room) temperature deviates from the medication storage temperature area of +15C° – +25C°. Typical installation locations are sun exposed areas, wind rooms and locations close to heating sources.

The standard product has 16 storage compartments in two columns of which 2 are large, 6 are mid-sized and 8 are small. One or two mid-sized compartments can be equipped with cool boxes for delivery of products requiring refrigeration.

Standard Climatop color is RAL9003 Signal white, all sides painted. Other whitish RAL-colors are available by order (see the spec below). About 25% of the exterior surface can be covered with multi-color stickers or printed graphics. Dark colors are not available. Please contact Remomedi sales for details.



Standard model 10111

Climatop model 10141

Climatop with Add-on locker,
32 doors

Remomedi is pharmacies’ partner in implementing omnichannel strategies including automated parcel delivery through locker stations. We offer turnkey solutions from product development to network operations and maintenance. Our unique solutions help pharmacies save money and offer the best customer experience for end-users.

Technical specifications

MODEL	Standard		Climatop Cool + Heat
Model number	10111		10141
Ambient temperature range for +15C° to +25C° storage			+5C° to +35C°
Doors	16 - 2 large, 6 mid-sized, 8 small in two columns		
Door customization	Yes		
Maximum number of doors	320 in one installation/location		
Add-on locker model number	10112		10142
Cool boxes	1 or 2 / locker		
Cool box temperature	+3C° to +7C°, nominal 5C° +/-1C°		
Temperature control	Build in multipoint + alerts		
Product size W x D x H [mm]	856 x 450 x 1851		856 x 450 x 2030
Weight [kg +/-0.5 kg]	166		190
Weight w/ one cool box [kg +/-0.5kg]	176		200
Weight w/ two cool boxes [kg +/-0.5kg]	186		210
Weight/m ² [kg +/-0.5kg]	99		112
Power supply	110V-230V, 50-60Hz		
Peak power consumption [W]	30		250
MECHANICS			
Build material	Steel - powder painted exterior, galvanized interior		
Exterior color	RAL 2003		
Optional colors	Any RAL	RAL9001, RAL9002, RAL9010, RAL9012, RAL9016, RAL9018	
Interior color	Metallic grey		
COOLING			
Refrigeration technology			Compressor
Refrigerant Climatop			R134a
Refrigerant Cool box			R600a
Coolant quantity max. [g]			100
Heating technology	x		Electro-resistive
USER INTERFACE			
Display	7 inch multitouch - no display on add-on locker		
Optical reader	1D and 2D scanning on mobile phone screens or paper		
COMMUNICATION			
Network connection	IoT 4G LTE or Cable		
Communication security	Encrypted one-way w/Stay-alive messaging		
BACKEND SW COMPATIBILY			
Standard	Remomedi PickupPharmacy and VideoPharmacy SW v1+		
Custom & Integrations	Remomedi White label PickupPharmacy Custom SW		

Remomedi is pharmacies' partner in implementing omnichannel strategies including automated parcel delivery through locker stations. We offer turnkey solutions from product development to network operations and maintenance. Our unique solutions help pharmacies save money and offer the best customer experience for end-users.